

Technical Data Sheet

Revised: 2022/03/11 (version 1.0)

PETRONAS TUTELA HYDROSYSTEM 68 AW



Description and Applications

PETRONAS Tutela HYDROSYSTEM 68 AW is premium performance anti-wear hydraulic fluids specially developed for a wide range of modern mobile and industrial hydraulic equipment operating under normal to extremely heavy-duty conditions including latest high speed and high-pressure systems. Developed with NEW HOLLAND and CASE/CASE IH for agricultural machinery in general and construction equipment.

Approvals, Specifications and Recommendations

Specifications:

- ISO VG 68
- DIN 51524 Part II HLP
- ISO 11158 HM

Approvals:

- CNH MAT 3529-B

Performance level:

- CNH MAT 3508-C
- NH 668
- BOSCH Rexroth RDE 90235
- EATON 03-401-2010/E-FDGN-TB002-E
- Fives Cincinnati P-68/P-69/P-70
- Parker Denison HF-0/HF-1/HF-2

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	--	--	Bright & Clear
Density @ 15°C	ASTM D 4052	g/cm ³	0.869
Kinematic Viscosity @ 40°C	ASTM D 445	mm ² /s (cSt)	69
Viscosity Index	ASTM D 2270	--	107
TAN	ASTM D 664	mgKOH/g	0.7
Pour Point	ASTM D 97	°C	-33
Flash Point COC	ASTM D 92	°C	255

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 81045