



## Mobilmet 760 Series

Mobil Industrial , Egypt

Oil-Based Cutting Fluids

### Product Description

Mobilmet 760 Series of lubricants are extra high performance oil-based cutting oils. They are chlorine-free and are intended for severe cutting operations especially on difficult to machine steels. They are corrosive-free and safe for copper and its alloys. In comparison with other leading premium cutting oils, Mobilmet 760 Series oils have demonstrated superior surface finish, extended tool life and control of built-up edge. Their light color enables the work area to be seen at all times. Closer tolerances are consistently achieved. The oils are formulated to prevent the formation of oil mist in the vicinity of the machine tool, thus contributing to a safe and more pleasant working environment.

With the benefit of comprehensive development testing using modern machining equipment, plus extensive customer evaluations, Mobilmet 760 Series products, have become the products of choice for many machine shops.

### Features and Benefits

The Mobilmet brand of cutting fluids has gained a well-deserved reputation for innovation and outstanding performance over the years. The Mobilmet 760 Series of lubricants are an important member of this family with their chlorine-free and low-misting additive technology. This formulation approach yields superior performance in a wide range of applications, while providing the environmental and disposal benefit of being chlorine-free.

Additional features and potential benefits of Mobilmet 760 products include:

Features	Advantages and Potential Benefits
Superb machining performance	Increased production resulting from longer tool life and reduced downtime for tool changes
	Improved surface finish, closer tolerances and reduced formation of built-up edge resulting in fewer rejects
Excellent lubricity	Cooler work pieces and increased feed rates possible for reduced operating costs

	s
Broad multi-purpose capability	Suitability for a wide range of severe machining operations on difficult steels
Light transparent colour	Provides a clear view of the tool and work piece
Anti-mist formulation	Improved workplace safety

## Applications

Mobilmet 760 Series of products are recommended for severe cutting operations on normal and difficult machine steels. Specific applications, by grade, include:

- Mobilmet 762 is particularly suitable for drilling, deep hole drilling (less than 20 mm diameter), threading, tapping, parting-off and automatic lathe operations on small work pieces
- Mobilmet 763 is recommended for deep hole drilling (greater than 20 mm diameter), drilling, tapping, threading, milling, gear shaping, broaching, parting-off and automatic lathe operations
- Mobilmet 766 is used for tapping, threading, milling, gear shaving and shaping, broaching, parting-off and automatic lathe operations

## Typical Properties

Mobilmet 760 Series	762	763	766
Kinematic Viscosity			
cSt @ 40°C	10.0	18.0	36.0
cSt @ 100°C	3.0	4.0	6.0
Flash Point, °C, COC	160	180	205
Specific Gravity @ 15°C kg/l, ASTM D 1298	0.87	0.87	0.88
Sulfur, Active	1.6	1.6	1.6
Chlorine	Nil	Nil	Nil

Anti-Mist Package	Present	Present	Present
Friction Modifier	Present	Present	Present

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of this product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobilmet are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2026 Exxon Mobil Corporation. All  
Rights Reserved